





REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2017-06-01



P.C.B LAYOUT

Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over 30-50u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PA6T/PA9T/LCP + 30%G.F

Electrical:

Current rating: 1.0Amps/contact max.

Contact resistance: ≤ 20mΩ/contact

Insulation resistance: ≥ 500MΩ at V=100V

Withstanding Voltage: 300V AC/minute

Mechanical:

Operating temperature: -40°C to +105°C

Wave soldering temperature: 255 ± 5°C, 10s

PROJECT	PA (mm)	H (mm)	PC (mm)
Standard	3.00	2.50	2.00
Specified			

PC11	2XX1	D	XX	X	B	N	X	DXXX
Product Descriptions PC11 H2.5 W3.0	No. of Positions 02-50P	Angle Type D Straight	Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag C PVC Box D Tube E Tube+CAP F Tape Reel G Reel+CAP	Series No. DXXX L=PA+H+PC

GSAMTEK® 东莞市广溯电子科技有限公司
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON	TITLE:
ANGLE ±5°	DATE: 2017-06-01	双排180度排针 PH1.27 H2.5 W3.0 系列图
X.XXX ±0.10	DRAWN: SAMTEK	PART NO. PC112XX1DXXXBNXDXXX
X.XX ±0.20	CHECKED:	DRAWING NO.
X.X ±0.30	APPROVED:	REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X ±0.50		

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2015-12-04

Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over30-50u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PA6T/PA9T/LCP+30%G.F

Electrical:

Current rating: 1.0Amps/contact max.

Contact resistance: $\leq 20\text{m}\Omega/\text{contact}$




Insulation resistance: $\geq 500\text{M}\Omega$ at $V=100\text{V}$

Withstanding Voltage: 300V AC/minute

Mechanical:

Operating temperature: -40°C to $+105^{\circ}\text{C}$

Wave soldering temperature: $255 \pm 5^{\circ}\text{C}, 10\text{s}$



P.C.B LAYOUT

PC11	2XX1	D	XX	X	B	N	X	D001
Product Descriptions PC11 H2.5 W3.0	No. of Positions 02-50P	Angle Type D Straight	Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag C PVC Box D Tube E Tube+CAP F Tape Reel G Reel+CAP	Series No. D001 L7.5mm PA3.0 PC2.0

GSAMTEK® 东莞市广溯电子科技有限公司
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON	TITLE:
ANGLE $\pm 5^{\circ}$	DATE: 2015-12-04	双排180度排针 PH1.27 H2.5 W3.0 L7.5 PA3.0 PC2.0
X.XXX ± 0.10	DRAWN: SAMTEK	PART NO. PC112XX1DXXXBNXD001
X.XX ± 0.20	CHECKED:	DRAWING NO.
X.X ± 0.30	APPROVED:	REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. ± 0.50		