





REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2015-06-08



## Specification

Material:  
 Contact Material: Brass  
 Contact plating: Au or Sn Over30-50u" Ni  
 Insulator Material: Black Polyester UL94V-0  
 Standard: PBT/PA6T/PA9T/LCP+30%G.F

Electrical:  
 Current rating: 2.0Amps/contact max.  
 Contact resistance: ≤ 20mΩ/contact  
 Insulation resistance: ≥ 1000MΩ at V=100V  
 Withstanding Voltage: 500V AC/minute





Mechanical:  
 Operating temperature: -40°C to +105°C  
 Wave soldering temperature: 255 ± 5°C, 10s

PROJECT	PA (mm)	PB (mm)	PC (mm)
Standard	4.00	0.75	2.8
Specified			

PD03	1XX1	R	XX	X	B	N	A	RXXX
Product Descriptions PD03 H2.0 W2.0	No. of Positions 02-40P	Angle Type R Right Angle	Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. DXXX L=PA+PB+PC+ H+W/2

<b>GSAMTEK® 东莞市广溯电子科技有限公司</b> DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD				
TOLERANCE ANGLE ±5° X.XXX ±0.10 X.XX ±0.20 X.X ±0.30 X. ±0.50	PROJECTON		TITLE: 单排90度排针 PH2.0 H2.0 系列图	
	DATE:	2015-06-08	PART NO. PD031XX1RXXXBNARXXX	
	DRAWN:	SAMTEK	DRAWING NO.	
	CHECKED:		REV: A0	UNIT: mm
APPROVED:				SIZE: A4

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2015-06-08



## Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over 30-50u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T/PA9T/LCP + 30%G.F

Electrical:

Current rating: 2.0Amps/contact max.

Contact resistance:  $\leq 20\text{m}\Omega/\text{contact}$

Insulation resistance:  $\geq 1000\text{M}\Omega$  at  $V=100\text{V}$

Withstanding Voltage: 500V AC/minute

Mechanical:

Operating temperature:  $-40^\circ\text{C}$  to  $+105^\circ\text{C}$





Wave soldering temperature:  $255 \pm 5^\circ\text{C}, 10\text{s}$

PD03	1XX1	R	XX	X	B	N	A	R001
Product Descriptions PD03 H2.0 W2.0	No. of Positions 02-40P	Angle Type R Right Angle	Contact Plated SN Tin120u" MT 锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. R001 L10.5mm PA4.0 PB0.75 PC2.8

**GSAMTEK® 东莞市广溯电子科技有限公司**  
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON		TITLE:
ANGLE $\pm 5^\circ$	DATE:	2015-06-08	单排90度排针 PH2.0 H2.0 L10.5 PA4.0 PB0.75 PC2.8
X.XXX $\pm 0.10$	DRAWN:	SAMTEK	PART NO. PD031XX1RXXXBNAR001
X.XX $\pm 0.20$	CHECKED:		DRAWING NO.
X.X $\pm 0.30$	APPROVED:		REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. $\pm 0.50$			

REVISION DATA		
REV	DESCRIPTION	DATE
		2018-12-11



## Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over 30-50u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T/PA9T/LCP + 30%G.F

Electrical:

Current rating: 2.0Amps/contact max.

Contact resistance:  $\leq 20\text{m}\Omega/\text{contact}$

Insulation resistance:  $\geq 1000\text{M}\Omega$  at  $V=100\text{V}$

Withstanding Voltage: 500V AC/minute

Mechanical:

Operating temperature:  $-40^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$

Wave soldering temperature:  $255 \pm 5^{\circ}\text{C}$ , 10s

PD03	1XX1	R	XX	X	B	N	A	R011
Product Descriptions PD03 H2.0 W2.0	No. of Positions 02-40P	Angle Type R Right Angle	Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. R011 L10.5mm PA2.8 PB0.75 PC4.0

**GSAMTEK® 东莞市广溯电子科技有限公司**  
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON	TITLE:
ANGLE $\pm 5^{\circ}$	DATE: 2018-12-11	单排90度排针 PH2.0 H2.0 L10.5 PA2.8 PB0.75 PC4.0 塑胶反向
X.XXX $\pm 0.10$	DRAWN: SAMTEK	PART NO. PD031XX1RXXXBNAR011
X.XX $\pm 0.20$	CHECKED:	DRAWING NO.
X.X $\pm 0.30$	APPROVED:	REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. $\pm 0.50$		