




REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2015-06-08



P.C.B LAYOUT

## Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over30-50u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T/PA9T/LCP+30%G.F

Electrical:

Current rating: 2.0Amps/contact max.

Contact resistance:  $\leq 20\text{m}\Omega/\text{contact}$

Insulation resistance:  $\geq 1000\text{M}\Omega$  at  $V=100\text{V}$

Withstanding Voltage: 500V AC/minute

Mechanical:

Operating temperature:  $-40^\circ\text{C}$  to  $+105^\circ\text{C}$

Wave soldering temperature:  $255 \pm 5^\circ\text{C}, 10\text{s}$




PROJECT	PA (mm)	H (mm)	PC (mm)
Standard	4.00	1.50	2.80
Specified			

PD02	2XX1	D	XX	X	B	N	A	DXXX
Product Descriptions PD02 H1.5 W4.0	No. of Positions 02-40P	Angle Type D Straight	Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. DXXX L=PA+H+PC

**GSAMTEK® 东莞市广溯电子科技有限公司**  
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON	TITLE:
ANGLE $\pm 5^\circ$	DATE: 2015-06-08	双排180度排针 PH2.0 H1.5 系列图
X.XXX $\pm 0.10$	DRAWN: SAMTEK	PART NO. PD022XX1DXXXBNADXXX
X.XX $\pm 0.20$	CHECKED:	DRAWING NO.
X.X $\pm 0.30$	APPROVED:	REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. $\pm 0.50$		

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2015-06-08



P.C.B LAYOUT

## Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over30-50u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T/PA9T/LCP+30%G.F

Electrical:

Current rating: 2.0Amps/contact max.

Contact resistance:  $\leq 20m\Omega$ /contact

Insulation resistance:  $\geq 1000M\Omega$  at V=100V

Withstanding Voltage: 500V AC/minute

Mechanical:

Operating temperature: -40°C to +105°C

Wave soldering temperature: 255±5°C, 10s

PD02	2XX1	D	XX	X	B	N	A	D001
Product Descriptions PD02 H1.5 W4.0	No. of Positions 02-40P	Angle Type D Straight	Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. D001 L8.3mm PA4.0 PC2.8

**GSAMTEK® 东莞市广溯电子科技有限公司**  
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON		TITLE:
ANGLE ±5°	DATE:	2015-06-08	双排180度排针 PH2.0 H1.5 L8.3 PA4.0 PC2.8
X.XXX ±0.10	DRAWN:	SAMTEK	PART NO. PD022XX1DXXXBNAD001
X.XX ±0.20	CHECKED:		DRAWING NO.
X.X ±0.30	APPROVED:		REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. ±0.50			