

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2016-04-16

Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over30-5u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T/PA9T/LCP+30%G.F

Electrical:

Current rating: 3.0Amps/contact max.

Contact resistance: $\leq 20m\Omega$ /contact

Insulation resistance: $\geq 1000M\Omega$ at V=100V





Withstanding Voltage: 1000V AC/minute

Mechanical:

Operating temperature: -40°C to +105°C

Wave soldering temperature: $255 \pm 5^\circ C, 10s$

PROJECT	PA (mm)	PC (mm)	PD (mm)
Standard	6.00	3.00	XXX
Specified			



P.C.B LAYOUT

PF05	2XXX	D	XX	X	B	N	A	DXXX
Product Descriptions PF05 H2.5 W5.0	No. of Positions 02-40P	Angle Type D Straight	Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. DXXX L=PA+PC+PD

GSAMTEK® 东莞市广溯电子科技有限公司
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON	TITLE:
ANGLE $\pm 5^\circ$	DATE: 2016-04-16	双排多塑180度排针 PH2.54 H2.5 系列图
X.XXX ± 0.10	DRAWN: SAMTEK	PART NO. PF052XXXDXXXBNADXXX
X.XX ± 0.20	CHECKED:	DRAWING NO.
X.X ± 0.30	APPROVED:	REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. ± 0.50		

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2016-04-16

Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over30-5u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T/PA9T/LCP+30%G.F

Electrical:

Current rating: 3.0Amps/contact max.

Contact resistance: $\leq 20\text{m}\Omega/\text{contact}$




Insulation resistance: $\geq 1000\text{M}\Omega$ at $V=100\text{V}$

Withstanding Voltage: 1000V AC/minute

Mechanical:

Operating temperature: -40°C to $+105^{\circ}\text{C}$

Wave soldering temperature: $255 \pm 5^{\circ}\text{C}, 10\text{s}$






P.C.B LAYOUT

PF05	2XX3	D	XX	X	B	N	A	D001
Product Descriptions PF05 H2.5 W5.0	No. of Positions 02-40P	Angle Type D Straight	Contact Plated SN Tin120u" MT 锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. D001 L17.0mm PA6.5 PC3.0 PD7.5

GSAMTEK® 东莞市广溯电子科技有限公司
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON		TITLE:
ANGLE $\pm 5^{\circ}$	DATE:	2016-04-16	双排三塑180度排针 PH2.54 H2.5 L17.0 PA6.5 PC3.0 PD7.5
X.XXX ± 0.10	DRAWN:	SAMTEK	PART NO. PF052XX3DXXXBNAD001
X.XX ± 0.20	CHECKED:		DRAWING NO.
X.X ± 0.30	APPROVED:		REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. ± 0.50			

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2018-07-10



Specification

Material:

Contact Material: Brass

Contact plating: Au or Sn Over30-50u" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T/PA9T/LCP+30%G.F

Electrical:

Current rating: 3.0Amps/contact max.

Contact resistance: $\leq 20\text{m}\Omega/\text{contact}$


Insulation resistance: $\geq 1000\text{M}\Omega$ at $V=100\text{V}$

Withstanding Voltage: 1000V AC/minute

Mechanical:

Operating temperature: -40°C to $+105^{\circ}\text{C}$

Wave soldering temperature: $255 \pm 5^{\circ}\text{C}, 10\text{s}$



P.C.B LAYOUT

PF05	2XX8	D	XX	X	B	N	A	D001
Product Descriptions PF05 H2.5 W5.0	No. of Positions 02-40P	Angle Type D Straight	Contact Plated SN Tin120u" MT 锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u"	Insulator Material A PBT C PA6T E PA9T F LCP	Insulator Color B Black	Insulator Feature N Without Peg	Packing Options A PE Bag	Series No. D001 L29.0mm PA6.0 PC3.0 PD20.0

GSAMTEK® 东莞市广溯电子科技有限公司
DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON		TITLE:
ANGLE $\pm 5^{\circ}$	DATE:	2018-07-10	双排八塑180度排针 PH2.54 H2.5 L29.0 PA6.0 PC3.0 PD20.0
X.XXX ± 0.10	DRAWN:	SAMTEK	PART NO. PF052XX8DXXXBNAD001
X.XX ± 0.20	CHECKED:		DRAWING NO.
X.X ± 0.30	APPROVED:		REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X. ± 0.50			