



P.C.B LAYOUT

| REVISION DATA | | |
|---------------|-------------|------------|
| REV | DESCRIPTION | DATE |
| A0 | NEW DRAWING | 2018-06-23 |

Specification

Material:
 Contact Material: Brass/Phosphor Bronze
 Contact plating: Au or Sn Over 30-50u" Ni
 Insulator Material: Black Polyester UL94V-0
 Standard: PBT/PA6T/PA9T/LCP + 30%G.F

Electrical:
 Current rating: 3.0Amps/contact max.
 Contact resistance: ≤ 20mΩ/contact
 Insulation resistance: ≥ 1000MΩ at V=100V
 Withstanding Voltage: 1000V AC/minute

Mechanical:
 Operating temperature: -40°C to +105°C
 Wave soldering temperature: 250 ± 5°C, 10s

| | |
|-----------|---------|
| PROJECT | PC (mm) |
| Standard | 2.6 |
| Specified | |

| | | | | | | | | | |
|--|----------------------------|-----------------------------|--|--|--|----------------------------|------------------------------------|---|---------------------------|
| FD06 | 2XX1 | R | XX | X | X | B | N | X | R00 |
| Product Descriptions FD06 H4.3 W4.0 | No. of Positions 02-40P | Angle Type R Right Angle | Contact Plated SN Tin120u" MT 雾锡120u" GF Gold 0.8u" G1 Au1u" G3 Au3u" G4 Au5u" G6 Au10u" G7 Au15u" G8 Au30u" GA Au1.5u" S1 半金锡1u" | Contact Material B Brass P Phosphor Bronze | Insulator Material A PBT C PA6T E PA9T F LCP | Insulator Color B Black | Insulator Feature N Without Peg | Packing Options B Tray C PVC Box D Tube E Tube+CAP F Tape Reel G Reel+CAP H Tube+Mylar I Reel+Mylar | Series No. R00 PC2.6mm |

GSAMTEK® 东莞市广溯电子科技有限公司
 DONGGUAN GUANG SU ELECTRONIC TECHNOLOGY CO.,LTD

| | | | |
|-------------|-----------|------------|---|
| TOLERANCE | PROJECTON | | TITLE: |
| ANGLE ±5° | DATE: | 2018-06-23 | 双排180度排母 PH2.0 H4.3 W4.0 U型 PB0.8 PC2.6 |
| X.XXX ±0.10 | DRAWN: | SAMTEK | PART NO. FD062XX1RXXXXBNXR00 |
| X.XX ±0.20 | CHECKED: | | DRAWING NO. |
| X.X ±0.30 | APPROVED: | | REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4 |
| X. ±0.50 | | | |